## Damage Resistant Re-centering Bridge Columns: Evaluation by Shake Table Testing

by

Marc Eberhard, U Washington Steve Mahin, UC Berkeley Claudia Ostertag, UC Berkeley Marios Panagiotou, UC Berkeley José Restrepo, UC San Diego

John Stanton, U Washington





**Project Manager:** Matt J. Schoettler, UC Berkeley

**OpenSees Support:** Vesna Terzic, PEER

#### **Students:**

Gabriele Guerrini, UC San Diego Olafur Haraldsson, U Washington Will Trono, UC Berkeley

#### **Richmond Field Lab Support:**

Wes Neighbour, Lab Manager Clement Barthes, Development Engineer David Maclam, Senior lab Mechanician Nate Knight, Lab Mechanician Russ Middleton, Lab Mechanician

#### **Volunteers:**

Yosuke Ishihara (UC Berkeley / Metropolitan Expressway Co., Japan) Gabe Jen (UC Berkeley)

Rotana Hay (UC Berkeley)

Hammad El Jisr (PEER Intern)



### **Program Objective**




Develop resilient bridge bent systems that:

- Re-center after a design earthquake,
- Have large lateral deformation capacities,
- Display low damage levels,
- Use conventional materials as much as possible,
- Allow pre-fabrication off-site,
- Are economical to build.



Conventional column



Damage resistant re-centering column

#### **Materials**

#### Damage resistance to be achieved using:

- Hybrid fiber reinforced concrete (HyFRC)
- Steel shells
- Stainless steel reinforcement
- Headed reinforcement







- Pre-tensioning with unbonded strands
- Post-tensioning with unbonded tendons or threaded bars











#### **Test Matrix**



#### Conventional RC column

Testing in December

- Benchmark, cast-in-place.
- Designed per Caltrans SDC v1.6
- A706 reinforcement

#### **UC Berkeley**

Steve Mahin Matt Schoettler Vesna Terzic



#### Precast/Prestressed column

- Precast, pre-tensioned
- HyFRC shell in the plastic hinge
- •A706 reinforcement

# Univ. of Washington John Stanton Marc Eberhard Olafur Haraldsson



#### HyFRC column

- ·Cast-in-place, post-tensioned
- •Precast HyFRC block at the base
- A706 reinforcement
- Rocking column

### UC Berkeley

Claudia Ostertag Marios Panagiotou Will Trono



#### Dual steel shell column

- Precast, post-tensioned
- Hollow inner shell
- •Stainless steel reinforcement
- Rocking column

<u>UC San Diego</u> José Restrepo Gabriele Guerrini




## Reinforcing Details of Test Specimens




#### Conventional RC column

Testing in December




#### Precast/Pre-tensioned column




#### HyFRC column

HyFRC PRECAST BLOCK — CONVENTIONAL MIX — (4) Ø0.6" PT STRAND (5) #5 A706 (DEBONDED) — (10) #5 HEADED — W4 SPIRAL @ 1.25" — 0.75" CLEAR ROCKING INTERFACE REMAINING DETAILING

#### Dual steel shell column



## **Preliminary test results**





## Pre-test view of the column base



#### Conventional RC column and CFRP column

Testing in December








## Damage: After design earthquake



#### Conventional RC column and CFRP column

Testing in December








## Damage: After 1.5\*design earthquake



#### Conventional RC column and CFRP column

Testing in December







## **Summary and Conclusions - 1**



- A family of resilient bent systems has been developed.
- Shake table tests conducted to investigate seismic performance.





#### **SEISMIC PERFORMANCE:**

- All the columns re-centered almost perfectly after 1.5\* design earthquake.
- No pre- or post-tensioning fractured.
- Some bars fractured at earthquake 7 (> 1.5\* Design)
- Damage to concrete/grout much less than in conventional columns.

EXCELLENT PERFORMANCE IN ALL THREE COLUMNS





#### MATERIALS USED

- HyFRC
- Concrete
- Grout
- Pre-stressing strand
- Pre-stressing bar
- A706 rebar
- Stainless steel rebar

ONLY HyFRC IS NON-STANDARD

## **Summary and Conclusions - 4**



#### CONSTRUCTION

- Some pre-fabrication in each column
- Each column used different connection methodology

## CONSTRUCTION PROCEDURES NEED TO BE OPTIMIZED FOR:

- \$peed
- \$implicity





















